Seal Tag

RFID tags with integrated fasteners prevent tampering with the contents of sealed containers

HID Seal Tag transponders are ideal for sealing commercial containers – bags, bins or boxes – to prevent unauthorized access to contents while in storage or during distribution. Seal Tag units integrate powerful RFID chips with high durability components, and secure, tamper-evident fasteners. Access to a sealed container's contents requires severing a tag's cable tie or wire loop – or breaching of the container itself – providing clear evidence of tampering.



VTAMPER TAGS

Each uniquely encoded Seal Tag vTamper RFID unit attaches anywhere a cable tie can be used, providing visual evidence when that seal is broken. Being waterproof, they have high resistance to aggressive liquids, UV rays, and temperature extremes. Thermoplastic polyurethane (TPU) housings tolerate repeated bending or torsion. Bright colors provide excellent contrast for optical identification when laser engraved or embossed with logos, barcodes or text. Highly rugged on-metal options exist as well.


ETAMPER TAGS

Each Seal Tag eTamper NFC transponder becomes operational when its wire loop is securely closed or the disc sticker is applied. If the wire loop is broken, the tag is permanently unreadable, leaving evidence detectable both visually and via RFID. The printable coin form factor features the same eTamper functionality: The antenna breaks when the coin is removed - ideal for "proof of presence" applications or payment schemes.

eTamper tags may also be used as an "intelligent" seal for life safety device cabinets, including fire extinguishers, automated external defibrillators (AED) or other equipment.

EDTAMPER TAGS

Seal Tag edTamper are tamper evident passive contactless Trusted Tag NFC or RAIN UHF transponders allowing detection of their seal status via RFID. Visualizing the tag is not necessary to identify broken seals. The edTamper tags-provide a digital notification if a seal has been compromised to quickly scan large sets of sealed items for integrity.



KEY BENEFITS:

- Security – RFID tags integrated into visually tamper-evident container seals
- Adaptability – Small and flexible to serve a wide range of applications
- Easy application – Attach quickly with integrated cable tie or wire loop
- Clear evidence – Visual recognition of seal status, with option of RFID reader detection of seal security or breach

TECHNOLOGY HIGHLIGHTS:

- Integrated, secure fastening device
- HF 13.56 MHz version readable with ISO/IEC 15693 or ISO/IEC 14443A compatible devices incl. NFC and HID Trusted Tag® Services
- Broadband RAIN UHF version for worldwide use at 860 to 960 MHz
- Fully interoperable, standards compliant
- Visually, electrically and digitally tamper evident options
- Custom encoding or laser engraving on housing

APPLICATION AREAS:

- Asset tracking and logistics
  - — Industrial bags, sacks and containers
  - — Merchandise distribution and retailing
  - — Life safety equipment maintenance
- Returnable transport items
  - — Reusable shipping vessels, bottles, cartons, bags, and canisters
- Waste management
  - — Hazardous waste receptacles

	Seal Tag						
	eTamper	vTamper			edTamper		
	Coin	HF	UHF	UHF Mini	HF	UHF	
							
Base Model Number	7A1941-001 (DESFire) 7H5941-101 (TTS)	629990-512	6M9990-500	6M9992-500	6I6503-101	6K2962	6K2963
	ELECTRONIC						
Operating Frequency	13.56 MHz		865-928 MHz (Global)		13.56 MHz	865-928 MHz (Global)	
Chip Type	MIFARE DESFire EV1 HID Trusted Tag (TTS)	ICODE SLIX2	M781		HID Trusted Tag (TTS)	EM4227 | AURA	
Memory	4.096 bytes (DESFire) 8.096 bytes (TTS)	1024 bit EEPROM	128 bit EPC, 512 bit user memory		144 byte EEPROM	2 kbit user memory + 416 bit EPC + 48 bit TID (Reserved: 32 bit Access password + 32 bit Kill password)	
Anti-Collision	Yes						
Reading Distance 2 W reader ERP, free space	N/A		20 ft (6 m)	Up to 13.1 ft (4 m)	N/A	Up to 13.1 ft (4 m)	
	PHYSICAL						
Dimensions	1.5 × 1.5 × 0.3 in (39 × 39 × 8.5 mm)	Tag: 3.3 × 1.0 × 0.1 in (85 × 25 × 3 mm) Cable tie: 15.0 × 0.3 × 0.1 in (380 × 6 × 2 mm)		Tag: 2.4 × 0.5 × 0.08 in (60 × 12 × 2 mm) Cable tie: 7.8 × 0.1 × 0.05 in (200 × 2.5 × 1.2 mm)	4.6 × 0.9 in (118 × 23 mm)	Tag: 1.73 x 0.65 x 0.14 in (44 x 16.5 x 3.7 mm) Seal wire: 3.07 in (78 mm)	Tag: 3.74 × 1.67 × 0.31 in (95 × 42.5 × 8 mm) Seal wire: 3.15 in (80 mm)
Mounting Method	Sticker	Integrated cable tie			Self-adhesive	Integrated wire loop	
Affixes To	Any material (hanging in free air)						On metal
Housing Material	Polycarbonate	Tag: TPU / Cable tie: Nylon 6.6		Tag: TPU / Cable tie: Nylon 6.6	Paper	PC/ABS	ABS
Color	Black (DESFire) White (TTS)	Tag: Yellow (Pantone 108) Cable tie: black		Tag: White Cable tie: Black	White		
Weight	0.18 oz (5.25 g)	0.42 oz (12 g)		0.08 oz (2.2 g)		0.08 oz (2.5 g)	1.13 oz (32 g)
	CHEMICAL AND MECHANICAL RESISTANCE						
Water	IP65	IP68, 68° F (20° C), 6.6 ft (2 m) x 24 h			IP67, 68° F (20° C), 3.3 ft (1 m) x 35 min		
Withstands Exposure To		Mineral oil, petroleum, salt mist, vegetable oil, HCL (10%), Bleach (5%); UV light					
Environmental Test Conditions	68° F (20° C), 100 h						
Flame Resistance						UL94V0 (self-extinguishing)	
Vibration	IEC 68.2.6 [10 g, 10 to 2000 Hz, 3 axis, 2.5 h]						
Shock	IEC 68.2.29 (40 g, 18 ms, 6 axis, 2000 times)						
Impact		IEC 62262-IK06		IEC 62262-IK06		IEC 62262-IK06	
Axial / Radial Force		1000 N, 10 sec				500 N, 10 sec	100 N, 10 sec
Pull Resistance	> 150 N	> 550 N		> 65 N	N/A	~ 35 N	> 30 N
Tag Bending	N/A	5.9 in (150 mm)		5.9 in (150 mm)	N/A		
	THERMAL						
Storage	-40° to +194° F (-40° to +90° C)	-40° to +158° F (-40° to +70° C)			On reel, Shelf life max. 1 year at 14° to 104°F (-10° to +40°C)	-40° to +158° F (-40° to +70° C)	
Operating	-13° to +158° F (-25° to +70° C)	-40° to +158° F (-40° to +70° C)			-4° to +158° F (- 20 °C to +70 °C)	-40° to +158° F (-40° to +70° C)	
Shock / Fatigue		-40° to +158° F (-40° to +70° C) , 100 x 5 min with 30 sec transition				-40° to +158° F (-40° to +70° C), 100 x 5 min with 30 sec transition	
	OTHER						
Standards	ISO/IEC 14443A, NFC Forum Type 4	ISO/IEC 15693, 18000-3 Mode 1, NFC Forum Type 5	UHF EPC Class 1 Gen 2, ISO 18000-6C		ISO/IEC 14443A, NFC Tag Type 2	UHF EPC Class 1 Gen 2, ISO 18000-6C, ATA Spec 2000 Chapter 9-5 (Version 2013), SAE AS5678 / DO-160	UHF EPC Class 1 Gen 2, ISO 18000-6C
Options	Printed Logo, Encoding, Color	Encoding, laser engraving, alternate colors					
Box Size	1,000 pcs	100 pcs.		300 pcs.	1,000 pcs	200 pcs	150 pcs
Warranty	2 Years						

hidglobal.com

North America: +1 512 776 9000 | Toll Free: 1 800 237 7769
Europe, Middle East, Africa: +353 91 506 900
Asia Pacific: +852 3160 9800 | Latin America: +52 55 9171 1108
For more global phone numbers click here

© 2026 HID Global Corporation/ASSA ABLOY AB. All rights reserved.

2026-09-28-idt-rfid-il-seal-tag-ds-en
Part of ASSA ABLOY

Supports GEN2X NFC RAIN

For more information, contact tagsales@hidglobal.com